

Specifikace LiPo Dualsky

Obj.č.	Typ	Napětí V	Kapacita mAh	Rozměry	Hmotnost
SL (16C)					
0734	600-3S SL (25/16C)	11,1	600	70x36x15	75
0474	2200-2S SL (25/16C)	7,4	2200	104x35x15,8	120
ES (20C, 2C)					
1305	110-1S ES (30/20C)	3,7	110	32x11x5	3
1306	250-3S ES (20/30C)	11,1	250	40x20x15	25
1091	2200-2S ES (30/20C)	7,4	2200	100x34,5x16	119
1093	3200-2S ES (30/20C)	7,4	3200	132x44x14	178
1094	3200-3S ES (30/20C)	11,1	3200	132x44x21	262
EX (30C, 5C)					
1272	400-2S EX (55/30C)	7,4	400	53x30x8,4	30
1273	400-3S EX (55/30C)	11,1	400	53x30x14	44
1274	800-2S EX (55/30C)	7,4	800	52x30x14	49
1275	800-3S EX (55/30C)	11,1	800	53x30x22,5	71
1297	1000-1S EX (55/30C)	3,7	1000	60x30x7,4	25
1276	1000-2S EX (55/30C)	7,4	1000	60x30x14,8	65
1277	1000-3S EX (55/30C)	11,1	1000	60x30x22,2	93
1278	1300-2S EX (55/30C)	7,4	1300	69x35x15	80
1279	1300-3S EX (55/30C)	11,1	1300	69x35x22,5	116
1280	1700-2S EX (55/30C)	7,4	1700	85x34x15,6	102
1281	1700-3S EX (55/30C)	11,1	1700	85x34x23,4	145
1282	2100-2S EX (55/30C)	7,4	2100	102x34x15	122
1283	2100-3S EX (55/30C)	11,1	2100	102x34x22,5	176
1284	2300-3S EX (55/30C)	11,1	2300	135x43x15	207
1285	2300-4S EX (55/30C)	14,8	2300	135x43x20	269
1286	2800-3S EX (55/30C)	11,1	2800	135x44x19	245
1307	2800-4S EX (55/30C)	14,8	2800	135x44x25	320
1287	2800-5S EX (55/30C)	18,5	2800	135x44x30	395
1288	2800-6S EX (55/30C)	22,2	2800	135x44x37	469
1289	4000-3S EX (55/30C)	11,1	4000	162x43x22,5	348
1290	4000-4S EX (55/30C)	14,8	4000	162x43x30	444
1291	4000-5S EX (55/30C)	18,5	4000	162x43x37,5	554
1292	4000-6S EX (55/30C)	22,2	4000	162x43x45	657
GT (25C, 2C)					
0761	300-3S GT (50/25C)	11,1	300	56x31x11,4	31
0765	1300-2S GT (50/25C)	7,4	1300	88x35x12	78
0747	2200-2S GT (50/25C)	7,4	2200	104x35x15,8	120
0853	3700-3S GT (45/22C)	11,1	3700	145x46x22	290
0770	3700-4S GT (45/22C)	14,8	3700	145x46x28	380
GT-S (35C, 2C)					
1144	2200-2S GT-S (60/35C)	7,4	2200	101x35,5x17	132
1145	2600-2S GT-S (60/35C)	7,4	2600	116x39,5x15	150
1146	3200-2S GT-S (60/35C)	7,4	3200	144x45x15,5	195
1149	3800-4S GT-S (60/35C)	14,8	3800	145x46x35,5	430
GT-S G5 (45C, 6C)					
1371	300-2S GT-S (45C)	7,4	300	52x30x7,2	23
1372	300-3S GT-S (45C)	11,1	300	52x30x10,6	34
1373	800-2S GT-S (45C)	7,4	800	52x31x15	53
1374	800-3S GT-S (45C)	11,1	800	52x31x22,5	78
1375	1200-2S GT-S (45C)	7,4	1200	64x31x17	76
1376	1200-3S GT-S (45C)	11,1	1200	64x31x25	115

1377	2250-2S GT-S (45C)	7,4	2250	101x35,5x17	132
1378	2250-3S GT-S (45C)	11,1	2250	101x35,5x26	193
1379	2250-6S GT-S (45C)	14,8	2250	101x35,5x50,5	362
1380	2650-3S GT-S (45C)	11,1	2650	126x39,5x23	219
1381	2650-4S GT-S (45C)	14,8	2650	126x39,5x31	286
1440	2650-5S GT-S (45C)	18,5	2650	126x39,5x38	357
1483	2650-6S GT-S (45C)	22,2	2650	126x39,5x45	418
1382	3250-3S GT-S (45C)	11,1	3250	144x48x23,2	287
1383	3250-4S GT-S (45C)	14,8	3250	144x48x30,5	368
1384	3250-5S GT-S (45C)	18,5	3250	144x48x38,2	463
1385	3700-3S GT-S (45C)	11,1	3700	145x48x27,3	331
1386	3700-4S GT-S (45C)	14,8	3700	145x48x35,5	430
1387	3700-5S GT-S (45C)	18,5	3700	145x48x44,2	535
1484	3700-6S GT-S (45C)	22,2	3700	145x48x53,5	636
1388	4450-3S GT-S (45C)	11,1	4450	160x50x26,5	636
1389	4450-4S GT-S (45C)	14,8	4450	160x50x35,5	491
1390	5000-5S GT-S (45C)	18,5	5000	175x50x46	662
1391	5000-6S GT-S (45C)	22,2	5000	175x50x55,5	785
1392	6000-5S GT-S (45C)	18,5	6000	195x51x41	735
1393	6000-6S GT-S (45C)	22,6	6000	195x51x49,5	882
Vysílačové					
0854	2500-3S vysílač JR	11,1	2500	95x30x25	150
0855	2500-3S vysílač Futaba	11,1	2500	95x30x25	150